

WTD-PRO67+MFW

Face Recognition Terminal



- Forced mask wearing alert: If the recognizing face does not wear a mask, the device will prompt a voice reminder. At the same time, the authentication or attendance will be failed
- Face mask wearing alert: If the recognizing face does not wear a mask, the device will prompt a voice reminder. At the same time, the authentication or attendance is valid
- 7-inch LCD touch screen, 2 Mega pixel wide-angle lens, built-in Proximity/Mifare card reading
- Face recognition distance (without face mask): 0.3 m to 3 m, Duration < 0.2 s/User, Accuracy rate ≥ 99%</p>
- Max.6000 faces, Max.6000 cards
- Two-way audio with client software, indoor station, and mainstation
- Supports TCP/IP
- Configuration via the web client
- Supports ISAPI and ISUP5.0 protocol
- IP65



WOT DIGITAL SERVICES PRIVATE LIMITED



Specification


System	
Operation system	Linux
Display	Lill MA
Dimensions	7-inch
Type	LCD
Operation method	Capacitive touch screen
Video	Capacitive touch screen
Pixel	2 MP
Lens	2
Audio	*:
Tone quality	Noise suppression and echo cancellation
Network	Noise suppression and echo cancellation
Wired network	10 M/100 M/1000 M celf adoptive
	10 M/100 M/1000 M self-adaptive
Interface	Ta .
Network interface	1
RS-485	1
Wiegand	1
Lock output	1
Exit button	1
Door contact input	1
IO input	2
IO output	1
Power interface	2-pin
TAMPER	1
USB	2
Capacity	
Card capacity	50,000
Face capacity	50,000 and Fingerprint Capacity: 5,000
Event capacity	2,00,000
Authentication	
Card type	Mifare 1 card
Card reading frequency	13,56MHz
Card reading distance	0 to 5 cm
Face recognition duration	< 0.2 s per person
Face recognition accuracy rate	≥ 99%
Face recognition distance	0.3 to 3 m (Without face mask)
Function	
QR code recognition	Support
Face anti-spoofing	Support
Advertisement	Support
Audio prompt	Support
Time synchronization	Support



General	
Power supply method	2-pin connecter
Power supply	12 VDC/2 A
Working temperature	-30 °C to 60 °C (-22 °F to 140 °F)
Working humidity	10 to 90% (No condensing)
Dimensions	239 mm × 116.5 mm × 33 mm (9.4" × 4.6" × 1.3")
Protective level	IP65
Installation	Surface
Language	English, Spanish (South America), Arabic, Thai, Indonesian, Russian, Vietnamese, Portuguese (Brazil)

Available Model WTD-PRO67+MFW

Dimension



Without Fingerprint Module





